


FEATURES

- Low power loss high efficiency
- Ideal for automated placement
- Guard ring for over-voltage protection
- High surge current capability



DO-214AC(SMA)



Schematic Symbol

APPLICATIONS

- Polarity: Color band denotes cathode end
- Mounting Position: Any

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter		Symbol	SS52A	SS53A	SS54A	SS55A	SS56A	SS58A	SS510A	SS515A	SS520A	Unit
Marking			SS52	SS53	SS54	SS55	SS56	SS58	SS510	SS515	SS520	
Repetitive peak reverse voltage		V _{RRM}	20	30	40	50	60	80	100	150	200	V
Reverse voltage,total RMS Value		V _{RMS}	14	21	28	35	42	56	70	105	140	V
Maximum DC blocking voltage		V _{DC}	20	30	40	50	60	80	100	150	200	V
Maximum average forward rectified current		I _{F(AV)} ¹⁾	5.0									A
Surge Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load per diode		I _{FSM}	100									A
Maximum Instantaneous forward voltage I _F =5A,T _a =25°C		V _F	0.55			0.70		0.85		0.95		V
Maximum DC reverse current at rated DC blocking voltage	T _A =25°C	I _R	0.5					0.1				mA
	T _A =100°C		10					5				mA
Typical thermal resistance Note 1		R _{θJA}	60 ¹⁾									°C/W
Typical thermal resistance Note 1		R _{θJL}	22 ¹⁾									°C/W
Operating junction temperature range		T _J	-55 to +150					-55 to +175				°C
Storage temperature range		T _{STG}	-55 to +150									°C

Note1): Mounted on PCB with 5.0x5.0mm copper pads.

CHARACTERISTIC CURVES

Fig. 1- I_o - TL Curve




Fig. 2-Surge Forward Current Capability




Fig. 3-Typical Forward Characteristics






Fig. 4-Typical Reverse Characteristics




SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak)		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C




DO-214AC(SMA) PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.20	1.60	0.047	0.063
B	4.20	4.60	0.165	0.181
C	2.60	2.80	0.102	0.110
D	2.10	2.40	0.083	0.094
E	0.76	1.52	0.030	0.060
F	0.02	0.20	0.001	0.008
G	4.85	5.25	0.191	0.207
H	0.15	0.30	0.006	0.012

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.63	-	0.064	-
B	1.45	-	0.057	-
C	-	2.80	-	0.090
D	1.45	-	0.057	-
E	5.28REF		0.208REF	

ORDERING INFORMATION

Part Number	Size	QTY/Reel	Reel Size
SS52A-SS520A	DO-214AC(SMA)	5000PCS	13"

To find your local partner within Semiwell's website : www.semiwell.com

© 2023 Semiwell Microelectronics Co.,Ltd.

The content of this document has been carefully checked and understood. However, neither Semiwell nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiwell does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiwell. Latest publications and a complete disclaimer can be downloaded from the Semiwell website. All trademarks recognized.